

SL-240C

Compact 16-Port Master / Room Controller with PoE

| WEB-CTRL



SL-240C is a compact master/space controller (Kramer Control brain) with PoE. It can operate over Ethernet with control interfaces that include: four bidirectional RS-232, four IR, four GPI/O, and four relays. It controls devices such as scalers, video displays, audio amplifiers, Blu-ray players, sensors, screens, shades, door locks, and lights. Multiple Kramer Ethernet control gateways can be used to add remote I/O ports

FEATURES

Space Controller - Controls any AV device/display with its corresponding logic

High Performance Architecture - Enables a scalable and flexible programming platform

4 RS-232 Bidirectional Control Ports - For controlling devices via bi-directional serial control protocols

4 IR Emitter & 1 IR Receiver Control Ports - Control devices via IR control protocols and learn commands from IR remotes

4 GPI/O Control Ports - Control devices via general purpose I/O ports, program configured as digital input, digital output or analog input interface for controlling sensors, door locks, audio volume and lighting control devices

4 Relay Control Ports - Control devices via relay contact closure, such as opening and closing drapes, shades, blinds, and projection screen scrolling

Resilient powering with PoE and optional PSU (not included)

Network Support - 10/100/1000Mbps Ethernet

LED Indicators - I/O port state and system status

Software Management Support - Kramer Control, API



TECHNICAL SPECIFICATIONS

BIDIRECTIONAL PORTS:	4 RS-232 serial on 3-pin terminal blocks, 4 GPI/O on 2-pin terminal blocks, 1 Ethernet on a RJ-45 connector, 1 mini-USB connector for firmware upgrade
	Ethemet on a No 45 connector, 1 mm OOD connector for mmware upgrade
INPUTS:	1 built-in IR sensor (for learning)
OUTPUTS:	4 IR out and 4 relays on 2-pin terminal block connectors
INDICATORS:	LED indicator for each port and function
PROCESSOR SPEED:	1GHz
MEMORY:	512MB RAM, 4GB Flash
POWER CONSUMPTION:	5V DC, 2A
POWER SOURCE:	PoE (for extra power resiliency, connect to the optional 5V DC power supply)
PRODUCT DIMENSION:	18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H
PRODUCT WEIGHT:	0.4kg (1.0lbs) approx
SHIPPING DIMENSION:	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H
SHIPPING WEIGHT:	1.0kg (2.2lbs) approx

